



Type	16606 101 421	Features (Technical)	
Designation	Aluminium Light F10 Pro	Super bright SMT cool white LED	
Battery required	2x AAA Alkaline battery	Convex focusing lens	
LED	1x Silan SLW3535AY4, CCT 6000-6500K	Push switch (High/Off/Low/Off/Strobe/Off)	
Luminous intensity	Spot: High: 45 lm (506 cd) Low: 4 lm (64 cd) Flood: High: 175 lm (121 cd) Low: 15 lm (12 cd)	Tactical operation when light on (Soft touch button when light on--High/Low/Strobe)	
Run Time	High 2 h Low 25 h Strobe 2 h	Reset to high mode if off longer than 20 s	
Range	45 m (calculated distance at maximum luminous intensity with an illuminance of 0.25 lux)	Twist head to focus beam (spot to flood or flood to spot)	
Material	Aluminum PC (Polycarbonate) Silicon Rubber (All contact parts made of bronze or nickel-plated steel)	Broad and consistent flood beam with ultra view area	
Weight	36.8 g	Comfortable handle with knurling pattern	
Dimensions		Bracket clip removal function	
A	133 mm	Eye risk group II	
B	16 mm	1 m Drop test	
C	20 mm	10,000 switch cycle life	
D	15.4 mm		

No publication or circulation of data to third parties without consent of VARTA Consumer Batteries